

MB05 MOUNTED BREAKER

STANLEY®



The new **MB05** is designed for years of dependable service. The wide flow range let's you go from your skidsteer to mini-excavator with ease. The skidsteer bracket has four positions to allow you to tackle floors and walls.

All models are ready to pin-on or bolt on a custom bracket for your pin grab coupler.



We COVER ALL THE ANGLES you need to get the job done
Four position skid steer mounting bracket

SPECIFICATIONS

Impact Energy Class	ft - lb	550
	J	750
Blows Per Minute	bpm	650 - 1550
Flow Range	gpm	10 - 22
	lpm	38 - 83
Hydraulic Operating Pressure	psi	1500 - 2000
	bar	100 - 140
System Relief Pressure (min. cracking)	psi	3000
	bar	207
Oil Temperatures (max.)	F	190
	C	88
Hose Diameter (min.)	inch	3/4
	mm	19
Adapter Fitting Size and Type	Male JIC 37 degree Flare 1-1/16x12 UNF	
Weight – Skid Steer Model (with tool)	lb	810
	kg	368
Weight – Side Plate Model (with tool)	lb	480
	kg	218
Length - Side pLate Model (with tool)	inch	53
	mm	1346
Tool Diameter	inch	2.6
	mm	67
Tool Working Length	inch	15
	mm	381
Main Accumulator Charge Pressure	psi	200 +/- 10
	bar	13.8 +/- 0.7
Sound Power Level (LW)	dBA	125
Carrier Size - Skidsteer	lb	4500 - 7000
	kg	2045 - 3182
Carrier Size - Excavator	lb	5000 - 8000
	kg	2273 - 3636
Carrier Size - Backhoe	lb	6000 - 11000
	kg	2727 - 5000