

Specifications

Model	M6060		M7060	
	4WD		4WD	
ROPS / CAB	HD / HDCC		HD / HDCC	HD12 / HDCC12
Engine	V3307-CR-TE4			
Type (Make : KUBOTA)	4 cylinder in-line, Common Rail System, direct Inject.			
No. of cylinders/Aspiration	4 / turbocharged			
Engine net power* HP (kW)	63.5 (47.4)	71 (53.0)		
PTO power HP (kW)	56 (41.7)	64 (47.7)		
Total displacement cu.in. (cc)	203 (3331)			
Rated engine RPM ROPS/CAB	2400			
Fuel tank capacity ROPS/CAB gal. (ℓ)	18.5 (70) / 23.8 (90)			
Alternator ROPS/CAB	45 Amp / 100 Amp			
Transmission	F8 / R8		F12 / R12	
No. of speeds	F8 / R8		F12 / R12	
Main gear shift	Fully synchronized (4 speed)		Fully synchronized (6 speed)	
Dual speed (Hi-Lo)	N / A			
Shuttle shift	Hydraulic-shuttle			
Main clutch type	Multiple wet disc			
Brake type	Mechanical wet disc		Hydraulic wet disc	
Differential lock (Front / Rear)	N/A / Mechanical		Limited Slip Differential / Mechanical	
4WD clutch type	Mechanical on-the-go		Mechanical on-the-go / Electro-Hydraulic on-the-go	
PTO	Live-independent PTO, electro-hydraulic clutch with brake			
Type	Live-independent PTO, electro-hydraulic clutch with brake			
Speed rpm	540 (540 / 540E:OPT)		540 / 540E	
Hydraulics	11.0 (41.6)		16.2 (61.5)	
Pump capacity (3-Point Hitch) ROPS/CAB gpm (ℓ /min.)	11.0 (41.6)		16.2 (61.5)	
3-Point Hitch	Telescopic lower link ends, Telescopic Stabilizers			
Category	I / II			
Control system	Position, draft (top link sensing) & mixed control			
Lift capacity at 24 in. behind lift point lbs. (kg)	3307 (1500)			
Cylinder type	Two external cylinders			
No. of standard remote valves	1 (2nd, 3rd & flow control valve optional)			
Other features	Bevel gear type			
4WD system	Bevel gear type			
Steering	Hydrostatic power steering			
Tilt steering	Standard			
Hood type / Pedal type	Full open, slanted, steel / Hanging			
Deck type (ISO-mounted w/rubber mat)	Semi-flat on ROPS models, full-flat on CAB models			
Panel type	Electronic			
Fender shape	Wide, round			
Standard tire size	16.9-28		9.5-24	16.9-30
Front	16.9-28		9.5-24	16.9-30
Rear	16.9-28		9.5-24	16.9-30
Dimensions & weight	138.0 (3505)			
Overall length ROPS models in. (mm)	138.0 (3505)		138.0 (3505)	
CAB models in. (mm)	138.0 (3505)		138.0 (3505)	
Overall height top of ROPS in. (mm)	96.9 (2460)	97.2 (2470)		97.2 (2470)
top of CAB in. (mm)	100.6 (2555)	101.0 (2565)		101.0 (2565)
Overall width (minimum) in. (mm)	73.0 (1860)			
Wheelbase ROPS models in. (mm)	83.1 (2110)			
CAB models in. (mm)	83.1 (2110)			
Crop clearance (Front axle) in. (mm)	18.1 (460)			
Tread width Front in. (mm)	55.9, 59.8 (1420, 1520)			
Rear in. (mm)	55.9-67.7 (1420-1720)			
Turning radius (w/o brake) ft. (m)	11.8 (3.6)			
Tractor weight ROPS models lbs. (kg)	5005 (2270)	5027 (2280)		5027 (2280)
CAB models lbs. (kg)	5358 (2430)	5380 (2440)		5380 (2440)

*SAE J1349

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment. Please contact your local Kubota dealer for warranty, safety or product information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.